

ZPD208A / ZPD216A

Eco Plus Series

iNNEKT

Innovative Technology



Model		ZPD208A	ZPD216A
System	Operation System	Embedded Linux	
	System Resource	Pentaplex function: live monitoring, recording, playback, backup & remote access	
	Control Mode	Front panel, USB mouse, IR remote control, Network	
Video	Input	8 channel , BNC	16 channel , BNC
	Standard	PAL (625line, 50f/s)	
	Output	1 CVBS, BNC 1VGA, 800x600, 1024x768, 1280x1024, 1440x990, 1920x1080P 1HDMI	
Audio	Input	2 channel, BNC	2 channel, BNC
	Output	1 BNC (1.0Vp-p, 75ohms)	
	Bidirectional Talk	1 channel for bidirectional talk input synchronously	
Display	Resolution	PAL, D1(704x576)	
	Tour Display	Support	
	Privacy Masking	Four zones for privacy masking for each channel	
Recording	Video Compression	H.264	
	Audio Compression	G.711A	
	Image Encoding	Adjustable encoding quality, variable code stream/fixed code stream	
	Support dual Stream	YES	
	Recording Resolution	2CH@D1 + 6CH@CIF (1~25 fps)	16ch CIF realtime
	Recording Mode	Manual, auto, motion detection, trigger events	
Dtection & Alarm	Trigger Events	Recording, PTZ, Tour, Email	
	Motion Detection	396 (22x18) detection zone, variable sensitivity levels	
	Capture	JPEG capture	
	Alarm	N/A	
Playback & Backup	Playback Channel	Full Channel Playback	
	Backup Mode	USB, HDD, Network backup	
Network	Ethernet	1 RJ-45 port (10M / 100M)	
	Network Functions	TCP, UDP, HTTP, RTP/RTSP, DHCP, PPPOE, DDNS, NTP	
	Remote Operation	Monitoring, PTZ control, playback, system setting, file download, log information	
Hard Disk	Hard Disk	2 SATA Port (1HDD up to 3TB)	
Auxiliary Interface	USB Interface	2 USB 2.0 ports, each on front / rear panel	
	RS485	Standard 485, half duplex, 3.81 binding port	
Environment	Power Supply	12V 4A	
	Power Consumption	10W (without HDD)	
	Working Environment	-10°C~+55°C 10% - 90%RH	
	Local Login	Username+Password	
	Dimension	1U, 360x250x44 (mm)	
	Weight	2Kg (without HDD)	
	Installation	Desk type	