

KPC139EA-H

H.R. 35 IR LEDs Camera



● FEATURES

- (1) High resolution of 600 TV Lines
- (2) High sensitivity in the dark environment, 0.1 Lux / F2.0, 0 Lux (IR ON)
- (3) Day and night features for 24-hour surveillance
- (4) Excellent image quality
- (5) IR distance: up to 25 meters with 35 IR LEDs
- (6) IP67, suitable for outdoor use

● SPECIFICATIONS*

| MODEL | KPC139EA-H |
|----------------------------|--|
| Pick-up Element | 1/3" H.R. Color CCD image sensor |
| Number of Pixels | 768(H) x 494(V) <NTSC> / 752(H) x 582(V) <PAL> |
| Resolution | 600 TVL |
| Min. Illumination | 0.1 Lux / F2.0, 0 Lux (IR ON) |
| IR LED | 35 units |
| IR Effective Range | 25 Meters |
| S/N Ratio | More than 48dB (AGC off) |
| Electronic Shutter | 1/60 (1/50) to 1/100,000 sec. |
| Lens | f3.6mm / F2.0 |
| Lens Angle | 92.6° |
| White Balance | ATW |
| AGC | Auto |
| IRIS Mode | AES |
| IP Rating | IP67 |
| Video Output | 1.0 Vp-p composite, 75Ω |
| Operating Temperature | 0°C~40°C |
| Power Source (±10%) | DC12V |
| Current Consumption (±10%) | 70mA (IR OFF), 400mA (IR ON) |
| Gross Weight (g) | 430 |
| Dimensions (mm)** | 142(H) x 75(Φ) |

* The specifications are subject to change without notice.

** Dimensional Tolerance: ± 5mm

Good Sensitivity in Low Illumination

KPC13x Series



Conventional



True Color

KPC13x Series



Conventional

